

# Acolan<sup>®</sup> ADD 250



Article No. 6271

Chemical resistant, wear resisting mixture of polymer beads for the production of slip retardant seal coats.

## Range of use:

When adding the polymer beads to the liquid sealing material, transparent or coloured slip resistant seal coats can be produced.

## Characteristic data of the product:

**Form:** solid  
**Colour:** transparent  
**Odour:** odourless

## Working directions:

Mix Acolan Add 250 with the premixed sealing material until streak-free and using appropriate tools. The mixture is then applied according to the working instructions of the Acolan/Viscacid coating material.  
Acolan Add 250 is suitable for single layer thickness < 200 µm only!

## Packaging, application rate and storing:

**Packaging:** 0,25 kg, 25 kg  
**Application rate:** up to 0.05 kg Acolan Add 250 for 1 kg binder  
**Shelf-life:** At least 12 months in closed containers, unmixed, stored cool but frost-free.

## Safety, ecology, disposal:

Further information concerning safety during transport, storage and handling as well as for disposal is found in the latest Safety Data Sheet.

The statements above are compiled from our field of production and according to the latest technological developments and application techniques. Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet.

Any statements made beyond the contents of this information must be confirmed in writing by the producer.

In all cases, our general conditions of sale are valid.

With the publication of this Technical Information Sheet all previous editions are no longer valid.