



Technical Information Sheet
Article No. 6747

Selectmix SBL

(Acolan SelectMix SBL)

Filler mixture with a special aggregate grading curve

Range of use

Selectmix SBL is a special filler for epoxy resins that are used for the production of highly filled flow covers or levelling layers.

Property profile

Because of the volume optimised composition of Select Mix SBL, the filler gives epoxy resin systems outstanding working properties:

- Neutral colour
- High wear resistance
- High degree of filling

Characteristic data of the product

Appearance:	white, cream coloured
State:	solid
Density:	2.65 g/cm ³ (grain density)

Notes

The maximum degree of filling and the drying time depends on the epoxy resin used, the thickness of the layer and the conditions at the building site.

Packaging, shelf-life

Packaging:
15 kg paper sacks

Shelf-life:

At least 12 months stored dry and cool but frost-free in closed, original bags.

Safety, ecology, disposal

Further information on safety when transporting, storing and handling as well as disposal and ecology is found in the latest Safety Data Sheet.

The statements above are compiled from our field of production and according to the latest technological developments and application techniques.

Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet. Any statements made beyond the contents of this information must be confirmed in writing by the producer.

In all cases, our general conditions of sale are valid. With the publication of this Technical Information Sheet all previous editions are no longer valid.

6747-TI-07.07



Remmers (UK) Limited Crawley
United Kingdom
Tel: +44(0) 845 373 0103
Fax: +44(0)845 373 0104
www.remmers.co.uk

Remmers (Far East) Pte. Ltd.
Singapore
Tel: +65 6 7410277
Fax: +65 6 7417158