

PRODUCT DATA

PRE-PAINT CLEANER

DESCRIPTION

RUST-OLEUM® Pre-paint Cleaner cleans and degrease surfaces before painting. Suitable for all types of surfaces. Not flammable, not corrosive and nearly odourless.

Concentrated Multi-Surface Pre-Paint Cleaner

- Effortlessly removes all organic and inorganic pollution
- No further rinsing is needed after wiping the surface; saves time (Tested by COT independent technical test institute)
- Makes surface anti-static to prevent dust and dirt adhesion
- Non-foaming, biodegradable formulation (certified by TNO test institute)

RECOMMENDED USES

Pre-paint Cleaner for all types of surfaces: floors, walls, doors, window frames, metal, windows, door frames, etc. Cleans, degreases and also removes nicotine stains. Makes the surface anti-static to prevent adhesion of dust prior to painting. Does not foam.

TECHNICAL DATA (20°C and 50% RH)

Density:	1,05 kg/liter
pH:	11,45
VOC-content:	0 g/l
Dilution:	Because of its concentrated composition, Pre-Paint Cleaner is very economical in use. Depending on the degree of contamination, the product should be diluted in a ratio of between 1:10 and 1:100. 1:10 ovens, motors, extremely dirty floors 1:20 kitchens, machines, gas stoves, garden furniture 1:50 paintwork, nicotine stains 1:100 windows, mirrors, sun-beds etc.

Usage

Theoretical:	Ca. 100 m ² /l at a dilution of 1 : 20
Practical:	Practical coverage depends on many factors such as porosity, roughness of the substrate, contamination level and dilution during application.

DIRECTION FOR USE

Shake well before use. Scrape off grease, oil, dirt and other pollution as much as possible. Dilute RUST-OLEUM® Pre-paint cleaner to the required mixture and apply on the surface. Rub with a brush or white nylon pad and allow to work in for several minutes if necessary. Then wipe thoroughly with a damp sponge or cloth. With stubborn soiling repeat the treatment or leave to work in longer, possibly with a higher concentration.

APPLICATION CONDITIONS

Temperature of air, substrate and material between 5 and 35°C.

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELF LIFE / STORAGE CONDITIONS

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 40°C.

Rust-Oleum Netherlands B.V.
Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info@rust-oleum.eu
www.rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S
11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)1 30 40 00 44
F +33 (0)1 30 40 99 80
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.
Rotterdam House
116 Quayside
Newcastle
NE1 3DY
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info@rust-oleum.eu
www.rust-oleum.eu