

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022

Version number 4 (replaces version 3)

Revision: 14.12.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **EPOXY ESD COLOR 2K KOMP B**

Article number: 6686

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product category PC9a Coatings and paints, thinners, paint removers

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

Remmers GmbH

Bernhard-Remmers-Str. 13

D-49624 Lönigen / Germany

Tel.: +49(0)5432/83-0

Fax: +49(0)5432/3985

Remmers (UK) Limited

Unit 4 , Lloyds Court

Manor Royal, Crawley – West Sussex RH10 9QU

fon +44 (0) 1293 594 010

fax +44 (0) 1293 594 037

##### Information department:

Product Safety department: Phone: +44 (0) 1293 594 010

Email: sales@remmers.co.ukk

#### 1.4 Emergency telephone number:

National Poisons Information Service (NPIS):

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300

outside USA and Canada: 001-703-527-3887

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4	H302 Harmful if swallowed.
Acute Tox. 4	H332 Harmful if inhaled.
Skin Corr. 1B	H314 Causes severe skin burns and eye damage.
Eye Dam. 1	H318 Causes serious eye damage.
Skin Sens. 1	H317 May cause an allergic skin reaction.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

##### Hazard pictograms



GHS05 GHS07

Signal word Danger

##### Hazard-determining components of labelling:

benzyl alcohol

m-phenylenebis(methylamine)

(Contd. on page 2)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022

Version number 4 (replaces version 3)

Revision: 14.12.2022

## Trade name EPOXY ESD COLOR 2K KOMP B

(Contd. of page 1)

3-aminomethyl-3,5,5-trimethylcyclohexylamine  
 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)  
 1-ethyl-3-methylimidazolium dicyanamide  
 phenol, styrenated

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

### Hazard statements

H302+H332 Harmful if swallowed or if inhaled.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

### Precautionary statements

P260 Do not breathe dusts or mists.

P280 Wear protective gloves / eye protection / face protection.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### 2.3 Other hazards

#### Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

## \* SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

**Description:** Mixture of the substances listed below with harmless additions.

Dangerous components [% w/w]:		
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-XXXX	benzyl alcohol ----- Acute Tox. 4, H302; Acute Tox. 4, H332	≥30-<40%
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50-XXXX	m-phenylenebis(methylamine) ----- Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412, EUH071	≥10-<20%
CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9 Reg.nr.: 01-2119514687-32-XXXX	3-aminomethyl-3,5,5-trimethylcyclohexylamine ----- Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1A, H317 ATE: LD50 oral: 1,030 mg/kg Specific concentration limit: Skin Sens. 1A; H317: C ≥0.001 %	≥10-<20%
CAS: 113930-69-1 NLP: 500-302-7	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine) ----- Acute Tox. 4, H302; Skin Sens. 1, H317	≥10-<20%
CAS: 370865-89-7	1-ethyl-3-methylimidazolium dicyanamide ----- Skin Sens. 1, H317	≥5-<10%
CAS: 69-72-7 EINECS: 200-712-3 Reg.nr.: 01-2119486984-17-XXXX	salicylic acid ----- Repr. 2, H361d; Eye Dam. 1, H318; Acute Tox. 4, H302	≥2.5-<3%
CAS: 61788-44-1 Reg.nr.: 01-2119486984-17-XXXX	phenol, styrenated ----- Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥1-<2.5%

(Contd. on page 3)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022

Version number 4 (replaces version 3)

Revision: 14.12.2022

## Trade name EPOXY ESD COLOR 2K KOMP B

(Contd. of page 2)

CAS: 2579-20-6 EINECS: 219-941-5 Reg.nr.: 01-2119543741-41-XXXX	1,3-Cyclohexanedimethanamine Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Aquatic Chronic 3, H412	≥1-<2.5%
CAS: 61788-44-1 Reg.nr.: 01-2119980970-27-XXXX	phenol, styrenated Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥1-<2.5%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43-XXXX	ethanol Flam. Liq. 2, H225; Eye Irrit. 2, H319	≥0.5-≤1%
CAS: 25513-64-8 EINECS: 247-063-2 Reg.nr.: 01-2119560598-25-XXXX	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.5-<1%
CAS: 113930-69-1 NLP: 500-302-7 Reg.nr.: 01-2119965162-39-XXXX	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine) Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Skin Sens. 1B, H317	≥0.25-≤0.5%
CAS: 112-53-8 EINECS: 203-982-0 Reg.nr.: 01-2119485976-15-XXXX	dodecan-1-ol Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Eye Irrit. 2, H319	≥0.25-≤0.5%
CAS: 112-72-1 EINECS: 204-000-3 Reg.nr.: 01-2119485910-33-XXXX	1-Tetradecanol Aquatic Chronic 1, H410; Eye Irrit. 2, H319	≥0.1-<0.25%

**Additional information** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

##### General information

When symptoms occur or in case of doubt, seek medical advice

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

##### After inhalation

Take affected persons into the open air and position comfortably

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

##### After skin contact

Wash immediately with water and soap and rinse thoroughly.

Wash off immediately with water.

**After eye contact** Rinse opened eye for several minutes under running water. Then consult doctor.

##### After swallowing

Call a doctor immediately.

Drink plenty of water and provide fresh air. Call a doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

symptomatic treatment

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing agents

Water spray jet

Carbon dioxide

(Contd. on page 4)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022

Version number 4 (replaces version 3)

Revision: 14.12.2022

Trade name **EPOXY ESD COLOR 2K KOMP B**

(Contd. of page 3)

Foam

Use fire fighting measures that suit the environment.

**5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

Formation of poisonous gases during heating or in fires.

**5.3 Advice for firefighters****Protective equipment:**

Wear self-contained breathing apparatus.

Body protection

Put on breathing apparatus.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Put on breathing apparatus.

Wear protective equipment. Keep unprotected persons away.

**6.2 Environmental precautions:**

Inform responsible authorities in case product reaches bodies of water or sewage system.

**6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

**6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Ensure good ventilation/exhaust in workplaces.

Avoid the formation of aerosols.

**Information about protection against explosions and fires:** Keep breathing equipment ready.**7.2 Conditions for safe storage, including any incompatibilities****Storage****Requirements to be met by storerooms and containers:** No special requirements.**Further information about storage conditions:** Keep container tightly closed.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Components with limit values that require monitoring at the workplace:****CAS: 64-17-5 ethanol**WEL | Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm**Additional information:** The lists that were valid during compilation were used as a basis.**8.2 Exposure controls****Appropriate engineering controls** No further data; see item 7.**Individual protection measures, such as personal protective equipment****General protective and hygienic measures**

Do not eat, drink or smoke while working.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evaluated by the employer depending on the types of operations and the local circumstances. If a risk assessment on-site shows that there is no risk for employees, the personal protective equipment is not required or the amount of the PPE can be adapted accordingly.

(Contd. on page 5)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022

Version number 4 (replaces version 3)

Revision: 14.12.2022

Trade name **EPOXY ESD COLOR 2K KOMP B**

(Contd. of page 4)

**Respiratory equipment:**

Filter A (brown)

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

**Hand protection**

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material**

Break through time: max. 240 min (DIN EN 374).

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye/face protection** Tightly sealed safety glasses.\* **SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information**

<b>Physical state</b>	Fluid
<b>Colour:</b>	clear
<b>Odour:</b>	Amine-like
<b>Odour threshold:</b>	Not determined.
<b>Melting point/freezing point:</b>	Not determined
<b>Boiling point or initial boiling point and boiling range</b>	Not determined
<b>Flammability</b>	Not applicable.
<b>Lower and upper explosion limit</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
<b>Flash point:</b>	>100 °C
<b>Ignition temperature:</b>	not applicable
<b>Decomposition temperature:</b>	Not determined.
<b>pH</b>	Not determined.
<b>Viscosity:</b>	
<b>Kinematic viscosity</b>	Not determined.
<b>dynamic at 20 °C:</b>	120 mPas
<b>Solubility</b>	
<b>Water:</b>	Not miscible or difficult to mix
<b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
<b>Vapour pressure:</b>	Not determined.
<b>Density and/or relative density</b>	
<b>Density at 20 °C:</b>	1.059 g/cm <sup>3</sup>
<b>Relative density</b>	Not determined.
<b>Vapour density</b>	Not determined.

**9.2 Other information****Appearance:****Form:** Fluid**Important information on protection of health and environment, and on safety.****Explosive properties:** Product is not explosive.**Solvent separation test** < 3 %**VOC EU** < 500 g/l

(Contd. on page 6)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022

Version number 4 (replaces version 3)

Revision: 14.12.2022

Trade name **EPOXY ESD COLOR 2K KOMP B**

(Contd. of page 5)

<b>Change in condition</b>	
<b>Evaporation rate</b>	Not determined.
<b>Information with regard to physical hazard classes</b>	
<b>Explosives</b>	Void
<b>Flammable gases</b>	Void
<b>Aerosols</b>	Void
<b>Oxidising gases</b>	Void
<b>Gases under pressure</b>	Void
<b>Flammable liquids</b>	Void
<b>Flammable solids</b>	Void
<b>Self-reactive substances and mixtures</b>	Void
<b>Pyrophoric liquids</b>	Void
<b>Pyrophoric solids</b>	Void
<b>Self-heating substances and mixtures</b>	Void
<b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
<b>Oxidising liquids</b>	Void
<b>Oxidising solids</b>	Void
<b>Organic peroxides</b>	Void
<b>Corrosive to metals</b>	Void
<b>Desensitised explosives</b>	Void

## SECTION 10: Stability and reactivity

**10.1 Reactivity** No further relevant information available.

**10.2 Chemical stability**

**Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

**10.3 Possibility of hazardous reactions** No dangerous reactions known

**10.4 Conditions to avoid** No further relevant information available.

**10.5 Incompatible materials:** No further relevant information available.

**10.6 Hazardous decomposition products:** No dangerous decomposition products known

## \* SECTION 11: Toxicological information

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity:** Harmful if swallowed or if inhaled.

**LD/LC50 values that are relevant for classification:**

**CAS: 100-51-6 benzyl alcohol**

Oral	LD50	1,620 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

**CAS: 1477-55-0 m-phenylenebis(methylamine)**

Oral	LD50	930 mg/kg (rat)
Dermal	LD50	>3,100 mg/kg (rabbit)

**CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine**

Oral	LD50	1,030 mg/kg (ATE)
		1,030 mg/kg (rat)
Dermal	LD50	1,840 mg/kg (rabbit)

**Skin corrosion/irritation:** Causes severe skin burns and eye damage.

**Serious eye damage/irritation:** Causes serious eye damage.

**Sensitisation:** May cause an allergic skin reaction.

**Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

**Carcinogenicity:** Based on available data, the classification criteria are not met.

**Reproductive toxicity:** Based on available data, the classification criteria are not met.

**STOT-single exposure:** Based on available data, the classification criteria are not met.

**STOT-repeated exposure:** Based on available data, the classification criteria are not met.

(Contd. on page 7)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022

Version number 4 (replaces version 3)

Revision: 14.12.2022

Trade name **EPOXY ESD COLOR 2K KOMP B**

(Contd. of page 6)

**Aspiration hazard:** Based on available data, the classification criteria are not met.**11.2 Information on other hazards**

<b>Endocrine disrupting properties</b>
None of the ingredients is listed.

\* **SECTION 12: Ecological information****12.1 Toxicity**

<b>Aquatic toxicity:</b>
<b>CAS: 1477-55-0 m-phenylenebis(methylamine)</b>
EC50/48h   15.2 mg/l (Daphnia magna)

**12.2 Persistence and degradability** No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

**12.7 Other adverse effects****Remark:** Harmful to fish**Additional ecological information:****General notes:**

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Harmful to aquatic organisms

\* **SECTION 13: Disposal considerations****Recommendation**

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

<b>European waste catalogue</b>	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
20 01 28	paint, inks, adhesives and resins other than those mentioned in 20 01 27

**Uncleaned packaging:****Recommendation:**

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

**SECTION 14: Transport information**

<b>14.1 UN number or ID number</b> <b>ADR, IMDG, IATA</b>	UN1760
<b>14.2 UN proper shipping name</b> <b>ADR</b>	1760 CORROSIVE LIQUID, N.O.S. (m-phenylenebis(methylamine), Trimethylhexamethylenediamine)
<b>IMDG, IATA</b>	CORROSIVE LIQUID, N.O.S. (m-phenylenebis(methylamine), Trimethylhexamethylenediamine)

(Contd. on page 8)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022

Version number 4 (replaces version 3)

Revision: 14.12.2022

Trade name **EPOXY ESD COLOR 2K KOMP B**

(Contd. of page 7)

<b>14.3 Transport hazard class(es)</b>	
<b>ADR</b>	
	
<b>Class</b>	8 (C9) Corrosive substances.
<b>Label</b>	8
<b>IMDG, IATA</b>	
	
<b>Class</b>	8 Corrosive substances.
<b>Label</b>	8
<b>14.4 Packing group</b>	
<b>ADR, IMDG, IATA</b>	II
<b>14.5 Environmental hazards:</b>	
	Not applicable.
<b>14.6 Special precautions for user</b>	
<b>hazard identification number:</b>	Warning: Corrosive substances. 80
<b>EMS Number:</b>	F-A,S-B
<b>Stowage Category</b>	B
<b>Stowage Code</b>	SW2 Clear of living quarters.
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	
	Not applicable.
<b>Transport/Additional information:</b>	
<b>ADR</b>	
<b>Limited quantities (LQ)</b>	1L
<b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
<b>Transport category</b>	2
<b>Tunnel restriction code</b>	E
<b>IMDG</b>	
<b>Limited quantities (LQ)</b>	1L
<b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
<b>UN "Model Regulation":</b>	UN 1760 CORROSIVE LIQUID, N.O.S. (M-PHENYLENEBIS(METHYLAMINE), TRIMETHYLHEXAMETHYLENEDIAMINE), 8, II

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Directive 2012/18/EU

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

**DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

(Contd. on page 9)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022

Version number 4 (replaces version 3)

Revision: 14.12.2022

Trade name **EPOXY ESD COLOR 2K KOMP B**

(Contd. of page 8)

**REGULATION (EU) 2019/1148****Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

**Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

**Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H361d Suspected of damaging the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH071 Corrosive to the respiratory tract.

**Classification according to Regulation (EC) No 1272/2008** Calculation method**Department issuing data specification sheet:** Product Safety department / EHS**Date of previous version:** 07.05.2020**Version number of previous version:** 3**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Liq. 2: Flammable liquids – Category 2  
 Acute Tox. 4: Acute toxicity – Category 4  
 Skin Corr. 1A: Skin corrosion/irritation – Category 1A  
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 Skin Sens. 1: Skin sensitisation – Category 1  
 Skin Sens. 1A: Skin sensitisation – Category 1A  
 Skin Sens. 1B: Skin sensitisation – Category 1B  
 Repr. 2: Reproductive toxicity – Category 2  
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1  
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3