





Clean FP

- Facade Cleaner Paste -

Cleaning paste for removing urban dirt

Availability			
Quantity per pallet	288	60	16
Packaging unit	12 x 1 kg	5 kg	30 kg
Type of container	Plastic bucket	Plastic bucket	Plastic bucket
Container code	01	05	30
Art. no.			
0666			

Application rate



Min. 0.1 kg/m² depending on the degree of soiling


Apply to a large enough trial area to determine the precise amount required.

Range of use



- Mineral building materials, apart from sand-lime brick and glazed surfaces
- Removes heavy urban soiling (soot, dust, industrial dirt, etc.)

Property profile







■ Does not run on vertical surfaces

Efficient application

Characteristic data of the product

Carrier material	Water
Viscosity	Approx. 1800 mPa·s
pH value (20 °C)	Approx. 5.0
Appearance	Yellowish

The values stated represent typical characteristic data of the product and are not to be understood as bindin product specifications.

Certificates

> Data sheet for ingredients

Possible system products

- > Funcosil FC (0711)
- Funcosil SNL (0602)





> Funcosil SN (0604)

Preparation

Substrate preparation

Mechanically remove coarse soiling.

Directions







Conditions for use

Temperature of the material, air and substrate: from min. +5 °C to max. +30 °C

Apply the material using suitable equipment.

Use a scrubbing brush to work the material again.

Exposure time 2-5 min.

Do not allow the material to dry.

Rinse off thoroughly from bottom to top, using plenty of water under pressure.

Remove cleaning agent until no residues remain.

If needed, repeat the application.

Tips on use

Do not pre-wet!

Take appropriate measures to protect adjacent building elements and materials that

should not come into contact with the product. Set up the necessary collection receptacles.

Notes

Cleaner residues may cause irreversible discolouration.

The applicable regulations and legal requirements must be observed.

The relevant test certificates must be observed when planning and carrying out work.

Always set up a trial area/trial areas first.

Tools / Cleaning



Scrubbing brush, surface brush, ceiling brush, lamb's wool roller, high-pressure cleaner

Clean tools with water immediately after use.

Storage / Shelf life





At least 36 months in unopened, original containers stored cool, dry and protected from frost.

Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal

Active ingredient residues and rinsing water that contains the active ingredients of the product must not be allowed to enter the surface water drainage system. Collect rinsing water and dispose of at a collection point or through the sewage system according to local regulations. For more information, see advisory leaflet DWA-M 370 on "Waste and sewage from the cleaning of and coating removal from facades".

The object must be reported to the relevant authorities.

Detergents Regulation (EC) No 648/2004

5 - 15% ammonium bifluoride





Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.